

Application Number: 10/738,348  
Art Unit: 2875

Page 2 of 5

# AMENDMENTS TO THE CLAIMS:

Please amend the claims with the ones provided in the listing below wherein status, amendments, additions and cancellations are indicated.

1. (Currently amended) A motor vehicle reverse assistance light comprising:  
5 a housing which is an inverted U-shaped shell that includes: ~~utilized to hold a socket;~~  
a receptacle and a locating tab formed inside said housing;  
a threaded sleeve at one end of said inverted U-shaped shell of said housing;  
10 a stepped seating rim in said threaded sleeve;  
a base which is a rectangular-shaped member that includes:  
a rod and an arcuate groove formed on ~~the~~ said rectangular-shaped member of the said base;  
~~the~~ said rod on ~~the~~ said base member which is engaged within ~~the~~  
15 said receptacle in ~~the~~ said housing shell so that said base ~~it~~ is rotatably conjoined to said housing it; a said locating tab in ~~the~~ said housing shell situated in ~~the~~ said arcuate groove on ~~the~~ said base member;  
a socket having wire leads disposed on one end;  
20 a lamp hood that is a screw-on tube with a transparent outer cover fastened onto a said threaded sleeve; and ~~which further consists of:~~  
~~a receptacle and a locating tab formed inside the said shell;~~  
~~a threaded sleeve at one end of the said shell; and~~

Application Number: 10/738,348  
Art Unit: 2875

Page 3 of 5

~~an LED~~ a light emitting diode bulb cluster set onto the said socket,  
which is then inserted inside said stepped seating rim in ~~the~~ said threaded  
sleeve of ~~the~~ said housing.

2. (Currently amended) ~~As mentioned in Claim 1 of the~~ The motor vehicle  
5 reverse assistance light in Claim 1, wherein of the invention herein, ~~the~~ said  
receptacle in the said housing shell includes:

a semicircular retaining edge and a pair or more slots along its the  
opening of said receptacle:

~~the~~ said rod on ~~the~~ said base member consisting of:

10 a rounded annular tip at the distal end:

a passage through the center:

~~the~~ said rounded annular tip on the said rod of the said base member  
which is rotatably coupled by means of ~~the~~ said semicircular retaining edge  
along the opening of ~~the~~ said receptacle in the said housing shell; and

15 ~~the~~ said wire leads ~~leading on the~~ said socket which are routed through  
~~the~~ said passage centered in the said rod of the said base member.

3. (Currently amended) ~~As mentioned in Claim 1 of the~~ The motor vehicle  
reverse assistance light in Claim 1, wherein of the invention herein, a  
channel is formed along the lower side of said base member that proceeds  
20 along one side of ~~the~~ said member up to the said passage in the center of ~~the~~  
said rod on ~~the~~ said member to facilitate the routing of ~~the~~ said wire leads  
from the rear side of ~~the~~ said socket to the reverse light switch and electrical  
ground connections.